



■ Suitable Bits and Drive

### 492-PZDX Pozidriv® Klinge

Product no.: 492-PZDX

|  |     |
|--|-----|
| Dimensions L x W x H (mm)                      | --- |
| Dimensions L x W x H (inches)                  | --- |
| Weight (approx.) in kg                         | --- |
| Voltage  | --- |
| Power  | --- |
| Channels                                       | --- |
| Temperature range (depends on tool) °C         | --- |
| Temperature range (depends on tool) °F         | --- |
| Temperature accuracy °C                        | --- |
| Temperature accuracy °F                        | --- |
| Temperature accuracy for hot air °C            | --- |
| Temperature accuracy for hot air °F            | --- |
| Temperature stability °C                       | --- |
| Temperature stability °F                       | --- |
| Equipotential bonding socket                   | --- |
| Display  | --- |
| Additional vacuum pump                         | --- |
| Max. hot air flow rate l/min (depends on tool) | --- |
| Capacity l/min                                 | --- |
| Max. vacuum                                    | --- |
| Interface                                      | --- |

**Weller Tools GmbH**  
Carl-Benz-Straße 2  
74354 Besigheim  
Germany

Phone: +49 (0) 7143 / 580-0  
Fax.: +49 (0) 7143 / 580-108  
Email: [info@weller-tools.com](mailto:info@weller-tools.com)  
Web: [www.weller-tools.com](http://www.weller-tools.com)