Zero Smog 4V Kit 2 Nozzle

Product no.: T0053665699N



Benefits

- Constant Flow Control (CFC) guarantees automatical air flow regulation for each working place independent of the connected workplaces
- Electronic filter control with optical and acoustical filter alarm
- Efficiency test via USB port
- 4 wheels to allow easy movement of the unit
- Remote control via RS 232 port
- Low noise level
- 4 kits available
- The fume extraction unit Zero Smog 4V is easy to install and operate. It is designed for use as a small central system. The kits supplied complete with flexible hose, arm and bracket, ready for installation at the workplace. A powerful, maintenance-free turbine provides continuous fume extraction at a maximum air extraction rate of 230 m3/h. With setting constant flow control the adjustable turbine speed avoiding unnecessary waste of suction power and saving energy.

Technical Data

Dimensions L x W x H (mm)	345 x 325 x 505
Dimensions L x W x H (inches)	13,58x12,79x19,88
Weight (approx.) in kg	19
Voltage	220 - 240 V, 50/60 Hz
Power	275 VA
Noise level (distance 1 m) dB(A)	< 48
Max. vacuum	---
Capacity m³/h	230
Pre-filter	Pre filter mat class F7
Compact filter	Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Chemisorb)
Max. capacity	1–4 workstations
RS232 interface (remote control)	All system functions can be operated and remotely monitored via the RS232 port.
USB port	on
WX-compatible	on

Weller Tools GmbH
Carl-Benz-Straße 2
74354 Besigheim
Germany

Phone: +49 (0) 7143 / 580-0
Fax.: +49 (0) 7143 / 580-108
Email: info@weller-tools.com
Web: www.weller-tools.com