

# Zero Smog 4V Adhesive fume filter

Product no.: T0053661699N



## Benefits

- › Constant Flow Control (CFC) guarantees automatical air flow regulation for each working place independent of the connected workplaces
- › Electronic filter control with optical and acoustical filter alarm
- › Efficiency test via USB port
- › 4 wheels to allow easy movement of the unit
- › Low noise level
- › 4 kits available
- › The fume extraction unit Zero Smog 4V (ZS 4V) is adapt with a wide band gasfilter to exhaust adhesive fume at glueing applications. A powerful, maintenance-free turbine provides continuous fume extraction at a maximum air extraction rate of 230 m<sup>3</sup>/h. With setting constant flow control the adjustable turbine speed avoiding unnecessary waste of suction power and saving energy.



### Technical Data

Dimensions L x W x H (mm)	345 x 325 x 505
Dimensions L x W x H (inches)	12, 59 x 12, 59 x 15, 55
Weight (approx.) in kg	19
Voltage	230 V / 50 Hz (120 V / 60 Hz)
Power	275 VA
Noise level (distance 1 m) dB(A)	48 dB (A)
Max. vacuum	---
Capacity m <sup>3</sup> /h	---
Pre-filter	Pre filter mat class F7
Compact filter	Wide band gas filter (50 % Active carbon + 50 % Chemisorb)
Max. capacity	1-4 workstations
RS232 interface (remote control)	All system functions can be operated and remotely monitored via the RS232 port.
USB port	on
WX-compatible	on