



- Preheating plate
- WHP 80 24 V - 80 Watt temperature controlled preheat plate
- Accessory for WT1, WT1H, WT2M, WD1, WD2, WD1M and WD2M soldering stations and WR rework units
- For preheating of electronic components and single sided PC board assemblies
- Compatible with lead free solders
- Precision temperature control / 150° F - 400° F (50° C - 200° C)
- Heated surface - 80 W: Heating plate - 3.15" x 1.97" / 80 mm x 50 mm

WHP 80 Preheating plate

Product no.: T0052702899N

| | |
|--|-------------------------|
| Dimensions L x W x H (mm) | 175 x 125 x 45 mm |
| Dimensions L x W x H (inches) | 6.89 x 4.92 x 1.77 Inch |
| Weight (approx.) in kg | --- |
| Voltage | 24 V |
| Power | 80 W |
| Channels | --- |
| Temperature range (depends on tool) °C | 66 - 204 |
| Temperature range (depends on tool) °F | 150 - 400 |
| Temperature accuracy °C | --- |
| Temperature accuracy °F | --- |
| Temperature accuracy for hot air °C | --- |
| Temperature accuracy for hot air °F | --- |
| Temperature stability °C | --- |
| Temperature stability °F | --- |
| Equipotential bonding socket | --- |
| Display | --- |
| Additional vacuum pump | --- |
| Max. hot air flow rate l/min (depends on tool) | --- |
| Capacity l/min | --- |
| Max. vacuum | --- |
| Interface | --- |