

Zero Smog 4V Adhesive fume filter

Product no.: T0053661299N



Benefits

- › Mobile fume extraction unit, extracts contaminants at up to 4 workplaces
- › Includes F7 fine dust pre-filter and wide band gas filter (50 % active carbon / 50 % Chemisorb)
- › Constant Flow Control (CFC) guarantees automatic air flow regulation for each working place independent of the connected workplaces, at the same time avoiding unnecessary waste of suction power and saving energy
- › Electronic filter control with optical and acoustic filter alarm enables efficient filter performance monitoring
- › A powerful, maintenance-free turbine provides continuous fume extraction



Technical Data

| | |
|----------------------------------|--|
| Dimensions L x W x H (mm) | 345 x 325 x 505 |
| Dimensions L x W x H (inches) | 12, 59 x 12, 59 x 15, 55 |
| Weight (approx.) in kg | 19 |
| Voltage | 120 V |
| Power | 275 VA |
| Noise level (distance 1 m) dB(A) | 51 |
| Max. vacuum | 2700 Pa |
| Capacity m ³ /h | --- |
| Pre-filter | --- |
| Compact filter | Wide band gas filter (50 % Active carbon + 50 % Chemisorb) |
| Max. capacity | 1-4 workstations |
| RS232 interface (remote control) | All system functions can be operated and remotely monitored via the RS232 port |
| USB port | on |
| WX-compatible | on |